



Product Data Sheet

ASPC C3+ CUT

PRODUCT DESCRIPTION:

C3+ cut has been manufactured as a byproduct of ethylene plant designed based on TECHNIP technology.

APPLICATIONS:

C3+ used for extraction of 1,3 Butadiene, Propylene...

PRODUCT PROPERTIES:

Typical Vapor Pressure: 14.01 Bara at 45°C.

Typical Density: 0.592 g/cm³

PRODUCT SPECIFICATION:

Component	Min.	Max.	unit	Test method
Acetylene	0.00	0.01	% wt	ASTM D2163
Ethylene	0.01	2	% wt	ASTM D2163
Ethane	5.70	9.69	% wt	ASTM D2163
MAPD	0.38	0.84	% wt	ASTM D2163
Propylene	14.36	21.54	% wt	ASTM D2163
Propane	1.59	3.59	% wt	ASTM D2163
1,3-Butadiene	29.73	37.93	% wt	ASTM D2163
C4s	11.02	15.42	% wt	ASTM D2163
C5 ~ C9	17.46	29.10	% wt	ASTM D2163
C10+	0.10	5.59	% wt	ASTM D2163
Total Sulfur	0.0	Max. 30	mg/lit-(liquid)	ASTM D 6667

TOXICITY AND SAFETY:

For more detailed information on handling, storage, safety parameters, refer to relevant MSDS of Components.

CONTACT US:

Tehran office: 7th Floor ,No.2551, Kian Tower, (on the corner of Shahid Naseri), Valiasr AVE, Tehran- Iran

Postal code: 1968643111
 Tel: (+9821) 88645201-7, 85920000

P.O.Box:15875-8393
 Fax: (+9821) 88645193

www. Aryasol.com

Email: sop@aspcpe.com

Note: this information is based on our current knowledge and experience .in view of many factors that may affect processing and application, this data does not relive processors from the responsibility of carrying out their own tests and experiments, neither does it imply any legally binding assurance of certain properties or of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.